# PV-30 ja PV-302 Fire hydrant cabinet, surface-mounted



PV-30

PV-302

#### Description

Basic model fire hydrant cabinets are manufactured from 1,25 mm steel and the reels are made from 1 mm galvanized steel. The cabinet has a welded back wall that strengthens the structure and a reinforced door. The doors open 180 degrees.

A surface-mounted cabinet can be partially sunk into the wall to the desired depth by using a separate flush-mounting frame.

## Standard

Manufactured according to EN 671-1 standard specifications.

## Surface finish

Epoxy powder-coated Standard colours: -grey (RAL 7040) -white (RAL 9016) -red (RAL 3020)

#### Hoses

- Fabric surface polyester/EPDM lightweight hose. Fulfils EN 694:2001 standard. Operating pressure: 1,2 MPa Burst pressure: 9 MPa
- 2. Nitrile/PVC fire hydrant hose reinforced with polyester webbing. Fulfils EN 694:2001 Type A Class 2 standard.

Operating pressure: 1,2 MPa Burst pressure: 4 MPa

The hose assembly is equipped with a spray nozzle.

### Reel

The reels are painted red. The hub of the reel is made from a special pressure-tested brass casting. The reel is equipped with a spring-reinforced feed hose, a spray nozzle and a 1" shut off valve.

#### Lock

The door is equipped with a special lock that is shielded by a breakable protective glass (picture on the right).



## Hose size alternatives

LVI-koodi	Malli	Väri
2953398	PV-30	white
2953408	PV-302	white

