

Heat-insulated fire hydrant cabinets with heating



Description

Basic model fire hydrant cabinets are manufactured from 1,25 mm steel and the reels are made from 1 mm galvanized steel. The cabinet has a welded back wall that strengthens the structure and a reinforced door. The doors open 180 degrees.

19 mm cell rubber insulation. Insulated double door. Thermostat controlled 200 W electric resistor (230 V). Otherwise, the dimensions and materials are same as the basic model.

Standard

Manufactured according to EN 671-1 standard specifications.

Surface finish

Epoxy powder-coated

Standard colours:

- grey (RAL 7040)
- white (RAL 9016)
- red (RAL 3020)

Hoses

1. Fabric surface polyester/EPDM lightweight hose. Fulfils EN 694:2001 standard.
 - Operating pressure: 1,2 MPa
 - Burst pressure: 9 MPa
2. Nitrile/PVC fire hydrant hose reinforced with a polyester webbing. Fulfils EN 694:2001 Type A Class 2 standard.

Operating pressure: 1,2 MPa

Burst pressure: 4 MPa

The hose assembly is equipped with a spray nozzle.

Reel

The reels are painted red. The hub of the reel is made from a special pressure-tested brass casting. The reel is equipped with a spring-reinforced feed hose, a spray nozzle and a 1" shut off valve.

Lock

The door is equipped with a special lock that is shielded by a breakable protective glass (picture on the right).



Cabinet size alternatives

Surface-model

| Code | Model | Size |
|---|----------|-------------|
| 2954910 | PV-102EL | 990x690x305 |
| 2954920 | PV-202EL | 690x990x305 |
| Hose and nozzle are not included in price. Max hose dimensions 19 mm/25 m or 25 mm/20 m, lightweight hose 19 mm/30 m or 25 mm/25 m. | | |

Surface-model

| Code | Model | Size |
|---|----------|--------------|
| 2954930 | PV-11EL | 790x790x365 |
| 2954940 | PV-112EL | 1150x790x350 |
| 2954950 | PV-212EL | 790x1150x365 |
| Hose and nozzle are not included in price. Max hose dimensions 19 mm/45 m or 25 mm/30 m, lightweight hose 19 mm/50 m or 25 mm/35 m. | | |

Dimensions



